

INDUSTRIAL COMPONENT DATA

KP HC-ALU 100 K4 C4 P6 2203574 PHOENIX CONTACT

Membrane keypad, self-adhesive, copper conduction technology,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: KP HC-ALU 100 K4 C4 P6



Manufacturer	PHOENIX CONTACT
MPN / Reference	KP HC-ALU 100 K4 C4 P6
Catalog number	2203574
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-6CA77392F7
Generated	2026-08-04

Product Overview

Membrane keypad, self-adhesive, copper conduction technology, 4 keys, embossed, 4 colors, connection cable: 47.3 mm, RM 1.0 mm, operating temperature -20°C ... 70°C

Self-adhesive membrane keyboard, copper control technology, 4 keys, with highlight, 4 colors, connection cable: 47.3mm, pitch: 1.0mm, operating temperature: 0°C... 45°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Membrane keypad, self-adhesive, copper conduction technology, 4 keys, embossed, 4 colors, connection cable: 47.3 mm, RM 1.0 mm, operating temperature -20°C ... 70°C

Key Commercial Data

Orderkey 2203574

Packing unit 1 pc

GTIN 4055626485270

Weight per Piece (excluding packing) 15.200 g

Custom tariff number 85340019

Country of origin HU (Hungary)

Product properties

Type KP HC-ALU 100 K4 C4 P6
Order No. 2203574
Mounting type adhesive
Number of positions 4
Number of keys 4
Number of colors 4
Number of socket pins 6
Technology Conductive silver technology
Embossing Dome embossing 11 x 11 mm
Dimensions
Dimensions 95 mm x 72 mm
Pitch 1 mm
Length 47.3 mm (Membrane cable)
Ambient conditions
Ambient temperature (storage/transport) -20 °C ... 70 °C
Ambient temperature (operation) -40 °C ... 80 °C
Packaging details
Pieces per package 1
Denomination packing units Pcs.
Classifications
eCI@ss
eCI@ss 5.1 27180506
eCI@ss 6.0 27180800
eCI@ss 7.0 27182702
eCI@ss 8.0 27182702
eCI@ss 9.0 27182702
ETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
ETIM for 2203574 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Material (EF002169)
Other
Surface finishing (EF006569)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KP HC-ALU 100 K4 C4 P6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.