

INDUSTRIAL COMPONENT DATA

UT 6-HESI (6,3X32) 3046401 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 6-HESI (6,3X32)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 6-HESI (6,3X32)
Catalog number	3046401
Category	Fuse terminal block
Minimum order	1 Pcs
Document ID	EO-4FE229AA63
Generated	2026-08-02

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/6.3 x 32, nominal voltage: 630 V, nominal current: 10 A, connection type: Screw connection, Sizing cross-section: 6 mm², cross-section: 0.2 mm²- 10 mm², mounting type: NS 35/7.5, NS 35/15, color: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 6,3 x 32, nom. voltage: 630 V, nominal current: 10 A, connection method: Screw connection, Rated cross section: 6 mm², cross section: 0.2 mm²- 10 mm², mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Fuse terminal block

Area of application Railway industry

Machine building

Plant engineering

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 1.31 W

Fuse G / 6,3 x 32

Maximum current with single arrangement 10 A

Maximum power dissipation max. 1.6 W (with single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (with single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Connection data Number of connections per level 2

Nominal cross section 6 mm²

Level 1 above 1 below 1

Screw thread M4

Tightening torque 1.5 ... 1.8 Nm

Stripping length 10 mm

Internal cylindrical gage A5

Connection in acc. with standard IEC 60947-7-3

Conductor cross section rigid 0.2 mm² ... 10 mm²

Cross section AWG 24 ... 8 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 10 mm²

Conductor cross section, flexible [AWG] 24 ... 8 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 6 mm²

Flexible conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 6-HESI (6,3X32) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.