

**INDUSTRIAL COMPONENT DATA**

# ME 45 UT/FE GN 2909358 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 45 UT/FE GN



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME 45 UT/FE GN                   |
| Catalog number  | 2909358                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-469CC51C99                    |
| Generated       | 2026-08-03                       |

## Product Overview

Mounting base housing

Rail box, Lower part of the housing with metal pin, with 2 FE contacts, high design, with ventilation slits, width: 45.2 mm, height: 99 mm, depth: 107.3 mm, color: green (6021), cross bridge: without bus connector, number of poles cross connector: not relevant

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Housing (HS)

## Additional Product Information

Key Commercial Data

Orderkey 2909358

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 660 (C-1-2013)

GTIN 4017918163310

Weight per Piece (excluding packing) 65.200 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Component housing

Housing material Polyamide

Color (RAL) green (6021)

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Length 99 mm

Height 114.5 mm

Width 45 mm

Depth 99 mm

Technical data

Power dissipation without gap 8.2 W

Power dissipation with 20 mm gap 16.5 W

Number of positions 32

8

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss  
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC  
13.231261501

ETIM for 2909358 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Closed

Housing connectable (EF003088)

No

Material (EF002169)

Other

Surface finishing (EF0065...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 45 UT/FE GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.