

INDUSTRIAL COMPONENT DATA

LP 2,5/ 1-L BU 1071730 PHOENIX CONTACT Connector, rated voltage: 800 V, rated current: 24 A, number of poles..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LP 2,5/ 1-L BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	LP 2,5/ 1-L BU
Catalog number	1071730
Category	Terminal block connector
Minimum order	50 Pcs
Document ID	EO-D7D37B2918
Generated	2026-08-06

Product Overview

Connector, rated voltage: 800 V, rated current: 24 A, number of poles: 1, connection type: Push-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm²- 4 mm², color: blue

Plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal plug

Number of positions 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 8 kV

Connection dataStripping length 8 mm ... 10 mm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.14 mm² ... 4 mm²

Cross section AWG 26 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²

Nominal current 24 A

Maximum load current 24 A (with 4 mm² conductor cross-section)

Nominal voltage 800 V

Nominal cross section 2.5 mm²

Connection cross sections directly pluggable

Conductor cross section rigid 0.5 mm² ... 4 mm²

Conductor cross section, rigid [AWG] 20 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.5 mm² ... 2.5 mm²

Conductor cross section, flexible [AWG] 14 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm² ... 2.5 mm²

Dimensions Width 5.2 mm

Height 18.6 mm

Depth 40.3 mm

Length 18.6 mm

Material specifications Color blue

Flammability rating according to UL 94 V0

Insulating material group I

Insulating material PA

Static insulating mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LP 2,5/ 1-L BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.