

INDUSTRIAL COMPONENT DATA

LP 2,5/10 1071721 PHOENIX CONTACT Connector, rated voltage: 800 V, rated current: 24 A, number of poles: 10,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LP 2,5/10



Manufacturer	PHOENIX CONTACT
MPN / Reference	LP 2,5/10
Catalog number	1071721
Category	Terminal block connector
Minimum order	25 Pcs
Document ID	EO-C6BAE43F39
Generated	2026-08-05

Product Overview

Connector, rated voltage: 800 V, rated current: 24 A, number of poles: 10, connection type: Push-in lever connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm²- 4 mm², color: gray

Connector, nominal voltage: 800 V, nominal current: 24 A, number of poles: 10, connection type: Push-in connection, Dimensioning section: 2.5 mm², cross-section: 0.14 mm²- 4 mm², color: grey

Plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 10, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal plug

Number of positions 10

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 8 kV

Connection dataStripping length 8 mm ... 10 mm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.14 mm² ... 4 mm²

Cross section AWG 26 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
Nominal current 24 A
Maximum load current 24 A (with 4 mm² conductor cross-section)
Nominal voltage 800 V
Nominal cross section 2.5 mm²
Connection cross sections directly pluggable
Conductor cross section rigid 0.5 mm² ... 4 mm²
Conductor cross section, rigid [AWG] 20 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.5 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm² ... 2.5 mm²
DimensionsWidth 51.5 mm
Height 18.6 mm
Depth 40.3 mm
Length 18.6 mm
Material specificationsColor gray
Flammability rating according to UL 94 V0
Insulating material group I
Insulating material PA
Static insulating mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LP 2,5/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.