

## INDUSTRIAL COMPONENT DATA

# LPO 4/E 3270519 PHOENIX CONTACT Branch connector, nominal voltage: 800 V, nominal current: 24 A, number of p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPO 4/E



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | LPO 4/E                       |
| Catalog number  | 3270519                       |
| Category        | Test plug for terminal blocks |
| Minimum order   | 50 Pcs                        |
| Document ID     | EO-8E55A70B9F                 |
| Generated       | 2026-08-05                    |

## Product Overview

Branch connector, nominal voltage: 800 V, nominal current: 24 A, number of poles: 1, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, colour: grey

Bypass connector, rated voltage: 800 V, rated current: 24 A, number of poles: 1, connection type: Push-in connection, Dimensioning section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: grey

Pick-up plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Test plug terminal block

Number of positions 1

Connection dataStripping length 8 mm ... 10 mm

Internal cylindrical gage A3

B3

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.14 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Cross section AWG 26 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Nominal current 24 A

Maximum load current 24 A (with a 2.5 mm<sup>2</sup> conductor cross section)

Nominal voltage 800 V

Nominal cross section 2.5 mm<sup>2</sup>

Connection cross sections directly pluggable

Conductor cross section rigid 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section, rigid [AWG] 20 ... 14 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Dimensions Width 6.2 mm

Height 18.5 mm

Depth 53.4 mm

Material specifications Color gray

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protect...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPO 4/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.