

INDUSTRIAL COMPONENT DATA

LPT 16/ 1-10,0 1119809 PHOENIX CONTACT Terminal block for printed circuit board, nominal current: 76 A, nomi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPT 16/ 1-10,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	LPT 16/ 1-10,0
Catalog number	1119809
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-F9C7DEC76D
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, nominal current: 76 A, nominal cross-section: 16 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: LPT 16/, pitch: 10 mm, connection type: Push-in lever connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.6 mm, packaging type: boxed

Printed circuit board terminal, rated current: 76 A, rated section: 16 mm², number of potentials: 1, Number of rows: 1, Number of poles per row: 1, item family: LPT 16/, pitch: 10 mm, connection type: Push-in lever connection, mounting: Wave welding, connection direction conductor/printed circuit board: 0 °, color: green, Pin layout: Linear pin arrangement, Pin length [P]: 3.6 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1119809 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

39.6 mm

Number of electrical connections (EF008252)

1

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

10 mm

Rated current I_n (EF008250)

76 A

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.75 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.75 mm²

Connectable conductor cross section multi-wired (EF007343)

16 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.7 mm

Length pin (EF006825)

3.6 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPT 16/ 1-10,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.