

INDUSTRIAL COMPONENT DATA

LPT 16/ 4-15,0-ZB MC BD PE-L3 1753975 PHOENIX CONTACT

Printed circuit board terminal, rated current: 76 A, r..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPT 16/ 4-15,0-ZB MC BD PE-L3



Manufacturer	PHOENIX CONTACT
MPN / Reference	LPT 16/ 4-15,0-ZB MC BD PE-L3
Catalog number	1753975
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-666C27F16F
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 76 A, rated voltage (III/2): 1000 V, rated cross-section: 16 mm², number of rows: 1, number of poles per row: 4, item family: LPT 16/, pitch: 15 mm, connection type: Push-in lever connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0°, color: multicolor, Pin arrangement: Zigzag pins W, Pin length [P]: 3.6 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPT 16/ 4-15,0-ZB MC BD PE-L3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.