

INDUSTRIAL COMPONENT DATA

LPT 2.5/ 3-5,0 BK 1815366 PHOENIX CONTACT Printed circuit board terminal, rated current: 24 A, rated voltage..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPT 2.5/ 3-5,0 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	LPT 2.5/ 3-5,0 BK
Catalog number	1815366
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-845643FC8C
Generated	2026-08-03

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of rows: 1, number of poles per row: 3, item family: LPT 2.5/, pitch: 5 mm, connection type: Push-in lever connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPT 2.5/ 3-5,0 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.