

INDUSTRIAL COMPONENT DATA

LPTA 16/ 2-15,0-ZB 1333870 PHOENIX CONTACT Terminal block for printed circuit board, nominal current: 76 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPTA 16/ 2-15,0-ZB



Manufacturer	PHOENIX CONTACT
MPN / Reference	LPTA 16/ 2-15,0-ZB
Catalog number	1333870
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-6B94EFB0E7
Generated	2026-08-04

Product Overview

Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal cross-section: 16 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: LPTA 16/, pitch: 15 mm, connection type: Push-in lever connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 30 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 3.6 mm, number of welding pins per potential: 3, packaging type: boxed

PCB terminal, rated current: 76 A, rated voltage (III/2): 1000 V, rated cross-section: 16 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, item family: LPTA 16/, pitch: 15 mm, connection type: Push-in lever connection, mounting: Wave soldering, conductor/PCB connection direction: 30°, Color: Green, Pin Arrangement: Zigzag Pins W, Pin Length [P]: 3.8mm, Packing Type: Boxed Packaging

PCB terminal block, nominal current: 76 A, rated voltage (III/2): 1000 V, nominal cross section: 16 mm², number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: LPTA 16/, pitch: 15 mm, connection method: Lever Push-in connection, mounting: Wave soldering, conductor/PCB connection direction: 30 °, color: green, Pin layout: Zigzag pinning W, Solder pin [P]: 3.6 mm, number of solder pins per potential: 3, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Terminals XL

Product type Printed circuit board terminal

Product family LPTA 16/
Number of positions 2
Pitch 15 mm
Number of connections 2
Number of rows 1
Number of potentials 2
Pin layout Zigzag pinning W
Solder pins per potential 3
Electrical propertiesNominal current I_N 76 A
Nominal voltage U_N 1000 V
Degree of pollution 3
Rated voltage (III/3) 1000 V
Rated surge voltage (III/3) 8 kV
Rated voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Rated voltage (II/2) 1000 V
Rated surge voltage (II/2) 6 kV
Connection dataConnection technology
Nominal cross section 16 mm²
Conductor connection
Connection method Lever Push-in connection
Conductor cross section rigid 0.75 mm² ... 16 mm² (Conductor connection with open terminal point)
1.5 mm² ... 16 mm² (Push-in connection)
Single-conductor/terminal point multi-stranded 0.75 mm² ... 16 mm²
Conductor cross section flexible 0.75 mm² ... 25 mm²
Conductor cross section AWG 18 ... 4
Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.75 mm² ... 10 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 4 mm² ... 6 mm²
Stripping length 18 mm ... 20 mm
MountingMounting type Wave soldering
Pin layout Zigzag pinning W
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC J...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPTA 16/ 2-15,0-ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.