

INDUSTRIAL COMPONENT DATA

LS-WMTB-V4A (48X8) 1450532 PHOENIX CONTACT Cable marker, Stainless steel plate, silver, unlabeled, labelable..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (48X8)



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-V4A (48X8)
Catalog number	1450532
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-3335CF3BC0
Generated	2026-08-03

Product Overview

Cable marker, Stainless steel plate, silver, unlabeled, labelable with: TOPMARK NEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 2.9 mm, Number of individual indexes: 24, text field height: 8 mm, text field width: 48 mm

Cable Marker, Stainless Steel Plate

Cable markings, Stainless steel label, silver, blank, markable with: TOPMARK NEO, TOPMARK LASER, mounting type: Mounting with clamp, cable diameter: > 2.9 mm, usable area: 48 x 8 mm, Number of labels: 24

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Technical characteristicsProduct PropertiesType Rectangle

Product Type Marking of conductors

Version Card format

Scouting

Number of Labels 24

Marking technology Direct laser printing

DimensionsWidth 8.5 mm

Length 66 mm

Material thickness 0.50 mm

External dimensions

Outer Diameter 4.6 mm ... 136 mm

Material Guidance Colours silver

Material V4A (1.4404; AISI 316L)

Components free of silicone, halogen and cadmium

Cable/Conductor Outer diameter of the cable > 2.9 mm

2.9 mm

Environmental and service life conditions Checking for materials that may affect lacquer adhesion

Control of materials that may affect the dispersion of the lacquer (LABS compliance) VW PV 3.10.7:2005-02

Result Successful test

Checking for materials that may affect lacquer adhesion

Control of materials that may affect the dispersion of the lacquer (LABS compliance) VDMA 24364-A1-L:2018-05

Result Successful test

Scratch test to determine scratch resistance

Control Specification (Based on the standard) DIN EN ISO 1518-1:2019-10

Requirement ≥ 5 N

Result Successful test

Scotch Tape Trial

Control Specification (Based on the standard) DIN EN ISO 2409:2013

Result Successful test

UV resistance

Control Specification (Based on the standard) DIN EN ISO 4892-2:2013-06

Result Successful test

Duration of the inspection 96 h

Method Artificial radiation with xenon arc lamps

Temperature storage

Control Specification IEC 60068-2-2:2007-07

Result Successful test

Duration 240 h

Control Temperature 350 °C

Temperature resistance

Contr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (48X8) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.