

INDUSTRIAL COMPONENT DATA

M23-7ES198AA600S 1628488 PHOENIX CONTACT Device connector for front wall, M23 PRO, angled rotatable, for sta..

Brand: PHOENIX CONTACT | Manufacturer Part Number: M23-7ES198AA600S



Manufacturer	PHOENIX CONTACT
MPN / Reference	M23-7ES198AA600S
Catalog number	1628488
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-69EA6F5541
Generated	2026-08-02

Product Overview

Device connector for front wall, M23 PRO, angled rotatable, for standard and ONECLICK fast locking system, M23, No. of pos.: 4+3+PE, type of contact: Socket, Crimp connection, flange dimensions: 28 mm x 28 mm

M23, Conect. plug. to be apar. front wall., M23 PRO, Swivel angle, for quick ONECLICK and standard lock, No. of poles: 4+3+PE, contact type: Female, Crimped connection, flange measurement: 28 mm x 28 mm, The item does not contain lead according to the RoHS II directive without the exception 6c (Pb< 0.1%)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1628488

Packing unit 1 pc

Catalog page Page 147 (C-2-2019)

GTIN 4055626622194

Weight per Piece (excluding packing) 120.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Drawings

Data of the insulating body

Environmental Product Compliance

Temperature range

Housing data

Classifications

Drawings

Dimensional drawing

Technical drawings can be found under Downloads

Dimensional drawing

Installation dimensions

Schematic diagram

Back to topTemperature range

Ambient temperature (operation) -40 °C ... 125 °C

Back to topData of the insulating body

Note Order information: Order crimp contacts 4 x Ø 1 mm, 4 x Ø 2 mm separately

Insulator material PA 6.6

Contact connection method Crimp connection

Type of contacts Socket

Application Power

Number of positions 8

Contact diameter of power contacts 2 mm

Litz wire cross section of power contacts min. 0.25 mm²

Litz wire cross section of power contacts max. 4 mm²

Rated current for power contacts 30 A

Additional text for max. connection cross section

Rated voltage of power contact 630 V

Rated surge voltage 6 kV

Overvoltage category III

Degree of pollution 3

Contact diameter of signal contacts 1 mm

Litz wire cross section of signal contacts min. 0.06 mm²

Litz wire cross section of signal contacts max. 1 mm²

Rated current of each signal contact at 25°C 9 A

Additional text for max. connection cross section

Rated voltage of signal contact 250 V

Rated surge voltage 4 kV

Overvoltage category III

Degree of pol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / M23-7ES198AA600S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.