

INDUSTRIAL COMPONENT DATA

MACX MCR-EX-AP-RTD-RTD-SP 1291955 PHOENIX CONTACT

Ex i-resistance insulator transformer is used for intrinsi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MACX MCR-EX-AP-RTD-RTD-SP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MACX MCR-EX-AP-RTD-RTD-SP
Catalog number	1291955
Category	Temperature transformer
Minimum order	1 Pcs
Document ID	EO-7B6DC65AB4
Generated	2026-08-06

Product Overview

Ex i-resistance insulator transformer is used for intrinsically safe service of Pt 100 heat resistors in the technology of 2, 3 or 4 conductors and resistance transmitters. The measured values at the Ex i input are transmitted 1:1 to the non-Ex i output. Standard configuration, 3-way separation, Push-in connection

Ex i, Resistance Isolating Transformer is used for the intrinsically safe service of Pt 100 resistance thermometers in the technology of 2, 3 or 4 resistance conductors and transmitters. The measured values at the input Ex i are transmitted 1:1 to the output at non-Ex i. 3-Way Separation, Push-in Connection

Ex i-Resistance isolator for intrinsically safe operation of Pt 100 resistance thermometers in 2, 3, or 4-conductor technology and resistance-type sensors. The values measured at the Ex i input are transmitted 1:1 to the non Ex i output. Standard configuration, 3-way isolation, Push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Technical dataNotesGeneral Accuracy, typically specified as a percentage of the basic measuring range at UN, 23°C

General Installation conditions influence the ambient temperature.

Please refer to the "Control cabinet installation instructions".

General Sensor set via DIP switches

General 2-conductor comparison set via DIP switch ADJ

Product propertiesProduct type Temperature transmitter

Product family MACX Analog

No. of channels 1

Electrical propertiesNo. of channels 1

Electrical isolation 3-way isolation

Signal transmission behavior In = Out

Temperature coefficient, typical $\leq 0.1\%$ (10 K)

Reverse polarity protection yes

Electrical isolation Input/output IEC/EN 60079-11

Standards/regulations IEC/EN 60079-11

Rated insulation voltage 375 VPP

Electrical isolation Input/power supply IEC/EN 60079-11

Standards/regulations IEC/EN 60079-11

Rated insulation voltage 375 VPP

Electrical isolation Input/error message output IEC/EN 60079-11

Standards/regulations IEC/EN 60079-11

Rated insulation voltage 375 VPP

Electrical isolation Input/configuration interface IEC/EN 60079-11

Standards/regulations IEC/EN 60079-11

Rated insulation voltage 375 VPP

Electrical isolation Output 1/output 2

Test voltage 350 V (50 Hz, 60 s)

Electrical isolation Output/supply

Test voltage 350 V (50 Hz, 60 s)

Electrical isolation Output/configuration interface

Test voltage 350 V (50 Hz, 60 s)

Electrical isolation Output/supply/error message output

Test voltage 350 V (50 Hz, 60 s)

Supply

Nominal supply voltage 24 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MACX MCR-EX-AP-RTD-RTD-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.