

INDUSTRIAL COMPONENT DATA

MACX MCR-EX-SL-UI-REL-SP 2906165 PHOENIX CONTACT

Limit value switch with Ex i input for active current and v..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MACX MCR-EX-SL-UI-REL-SP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MACX MCR-EX-SL-UI-REL-SP
Catalog number	2906165
Category	Isolation amplifier
Minimum order	1 Pcs
Document ID	EO-F6B23A6B08
Generated	2026-08-01

Product Overview

Limit value switch with Ex i input for active current and voltage signals and a limit-value relay output (changeover contact). Can be set via DIP switch and potentiometer, galvanic 3-way electrical isolation, up to SIL2 (SC3), PLc Cat.1, Push-in connection.

Limit value switch with intrinsically safe input for active voltage and current signals and a limit value relay output (switched contact). Adjustable with DIP switch and potentiometer, 3-way galvanic separation, up to SIL2 (SC3), PLc cat.1, push-in connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2906165

Packing unit 1

Catalog page Page 168 (C-5-2019)

GTIN 4055626043739

Custom tariff number 85437090

Drawings

Ambient conditions

Output data

Connection data

General

Standards and Regulations

Classifications

Dimensions

Input data

Power supply

Connection data 2

Safety data

Environmental Product Compliance

Drawings

Pictogram

[Back to top](#)Dimensions

Width 12.5 mm

Height 99 mm

Depth 114.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 65 °C (Any mounting position)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Maximum altitude ≤ 2000 m

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Degree of protection IP20

Noise immunity EN 61000-6-2 When being exposed to interference, there may be minimal deviations.

[Back to top](#)Input data

Signal input Intrinsically safe

Voltage input signal 0.1 V ... 10 V

Current input signal 0.2 mA ... 20 mA

0.18 mA ... 21 mA (Maximum range)

Input resistance of voltage input > 100 kΩ

Input resistance current input < 28 Ω

Switching hysteresis off: approx. 0.5 %, on: approx. 1 %

Line fault detection Break U

Short circuit U > 10.8 V, I > 21.1 mA

[Back to top](#)Output data

Output name Relay output

Contact type 1 PDT

Contact material AgSnO₂, hard gold-plated

Max. switching current ≤ 4 A AC (cos φ = 1)

≤ 1 A DC (ohmic load, 24 V DC, 50 mW)

≤ 0.2 A DC (ohmic load, 120 V DC)

Mechanical service life ≤ 10⁷ cycles

[Back to top](#)Power supply

Nominal supply voltage 24 V DC

Supply voltage range....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MACX MCR-EX-SL-UI-REL-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.