

INDUSTRIAL COMPONENT DATA

FL SWITCH 4008T-2SFP 2891062 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 4008T-2SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 4008T-2SFP
Catalog number	2891062
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-17C53171A8
Generated	2026-08-06

Product Overview

Industrial Ethernet Switch

Managed Ethernet switch with eight RJ45 ports for 10/100 Mbps and two SFP ports for 1000 Mbps. Wide range of usage temperatures of -40°C... +75°C.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2891062

Packing unit 1 pc

Catalog page Page 410 (C-6-2017)

GTIN 4046356764308

Weight per Piece (excluding packing) 1,280.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 54.4 mm

Height 146.4 mm

Depth 125 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 8 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m

Interface 2 Fiber optic interface

No. of ports 2 (SFP ports)

Transmission physics multi-mode fiberglass

Transmission speed 1000 Mbps (full duplex)

Transmission length up to 80 km (Depending on the fiber/SFP module used)

Function

Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 4008T-2SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.