

INDUSTRIAL COMPONENT DATA

FL SWITCH 3006T-2FX SM 2891060 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 3006T-2FX SM



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 3006T-2FX SM
Catalog number	2891060
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-D70EE2876A
Generated	2026-08-05

Product Overview

Industrial Ethernet Switch

Ethernet managed switch with six RJ45 ports for 10/100 Mbps/s, two ports for fiber optics in SC format and an operating temperature of -40 °C ... +75 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > I/O**

Additional Product Information

Key Commercial Data

Orderkey 2891060

Packing unit 1 pc

Catalog page Page 409 (C-6-2017)

GTIN 4046356764285

Weight per Piece (excluding packing) 960.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Dimensional drawing

Width 54.4 mm

Height 146.4 mm

Depth 125 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 6 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m

Interface 2 Fiber optic interface

No. of ports 2 (SC single mode)

Transmission physics Single-mode fiberglass

Transmission speed 100 Mbps (full duplex)

Transmission length 40 km (fiberglass with F-G 9/125 0.36 dB/km)

Wavelength 1300 nm

Function

Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x secur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 3006T-2FX SM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.