

INDUSTRIAL COMPONENT DATA

SK 2,8 REEL P2,54 WH CUS 0825120 PHOENIX CONTACT

Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 2,8 REEL P2,54 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK 2,8 REEL P2,54 WH CUS
Catalog number	0825120
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-602D2E8A59
Generated	2026-08-05

Product Overview

Marker card

Strip card, available: per card, white, labelled according to customer specifications, mounting type: glued, for terminal width: 2.54 mm, usable surface: endless x 2.8 mm

Marker card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, for terminal block width: 2.54 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled terminal marker

Pitch 2.54 mm

Type Label

Data management status

Article revision 01

Marking

Number of marker strips 14

MountingMounting type adhesive

Material specificationsFoil strength 53 µm

Adhesive strength 20 µm

Adhesive Acrylic

Color white (RAL 9010)

Material Polyester

Components free from silicone and halogen

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 15 °C

Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

Shelf life 12 months

Dimensions Height 2.8 mm

Pitch 2.54 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Notes Order information: Marking up to max. 25-pos.

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 2,8 REEL P2,54 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.