

INDUSTRIAL COMPONENT DATA

SK 5/3,8:UNBEDRUCKT 0805409 PHOENIX CONTACT Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 5/3,8:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK 5/3,8:UNBEDRUCKT
Catalog number	0805409
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-8D40EF5BCB
Generated	2026-08-05

Product Overview

Marker card

Strip card, white, unlabeled, labelable with: Special marker: without printing, mounting class: glued, for terminal width: 5 mm, useful surface: 5 x 3.8 mm, Number of individual indexes: 120

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 0805409

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 502 (CL-2009)

GTIN 4017918129187

Weight per Piece (excluding packing) 0.710 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Width (a) 5 mm

Height (c) 3.8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 15 °C

Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.

General

Note Can be labeled with CMS

Color white

Type adhesive

Components free from silicone and halogen

Material Polyester

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of marker strips 12

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 5/3,8:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.