

**INDUSTRIAL COMPONENT DATA**

# SK U/3,8 WH:UNBEDRUCKT 0803906 PHOENIX CONTACT

## Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/3,8 WH:UNBEDRUCKT



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | SK U/3,8 WH:UNBEDRUCKT       |
| Catalog number  | 0803906                      |
| Category        | Labelling for terminal block |
| Minimum order   | 10 Pcs                       |
| Document ID     | EO-BC2BDC92D1                |
| Generated       | 2026-08-03                   |

## Product Overview

### Marker card

Strip card, DIN A4, white, unlabelled, labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting class: glued, for terminal width: 210 mm, usable surface: 186 x 3.8 mm, Number of individual indexes: 1440

Marking card, Din A4, white, blank, can be labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: glue, for clamp thickness: 210 mm, Number of individual tags: 1440, height of the text field: 3.8 mm, width of the text field: 186 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

### Key Commercial Data

Orderkey 0803906

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 159 (C-3-2017)

GTIN 4017918007799

Weight per Piece (excluding packing) 13.130 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 186 mm

Width (a) 3.8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 0 °C

Recommended storage conditions 20-25 °C / 40-50 % relative humidity.

General

Note Print image may vary depending on laser printer

Color white

Type adhesive

Components free from silicone and halogen

Material Polyester

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 1440

Number of individual labels per row 36

Number of marker strips 40

Adhesive Acrylic

Printability Office printing systems

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO<sub>2</sub> test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Adhesive strength 20 µm

Marking mounting type adhesive

S...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/3,8 WH:UNBEDRUCKT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.