

INDUSTRIAL COMPONENT DATA

SK U/5,0 WH:UNBEDRUCKT 0803922 PHOENIX CONTACT

Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/5,0 WH:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U/5,0 WH:UNBEDRUCKT
Catalog number	0803922
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-8265611AEC
Generated	2026-08-04

Product Overview

Marker card

Strip card, DIN A4, white, unlabelled, labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: glued, for terminal width: 210 mm, usable surface: 186 x 5 mm, Number of individual indexes: 630

Marker card, Din A4, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: adhesive, for terminal block width: 210 mm, Number of individual labels: 630, text field height: 5 mm, text field width: 186 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral Print image may vary depending on laser printer

Product propertiesProduct type Terminal marking

Pitch 210 mm

Type Label

Data management status

Article revision 07

Marking

Number of individual labels 630

Number of individual labels per row 18

Number of marker strips 35

Identification technology Office laser printing

DimensionsText field width 186.00 mm

Height 5 mm

Text field height 5.00 mm

Length 186 mm

Pitch 210 mm

Material specificationsFoil strength 50 µm

Adhesive strength 20 µm

Adhesive Acrylic

Color white (RAL 9010)

Material Polyester

Components free from silicone and halogen

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 200 °C (230 °C) Test passed

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-01):2020-03

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Tes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/5,0 WH:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.