

**INDUSTRIAL COMPONENT DATA**

# STP 4-2 0810575 PHOENIX CONTACT Marker carriers

Brand: PHOENIX CONTACT | Manufacturer Part Number: STP 4-2



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | STP 4-2                         |
| Catalog number  | 0810575                         |
| Category        | Mounting for labelling material |
| Minimum order   | 100 Pcs                         |
| Document ID     | EO-E0CD5B0C6F                   |
| Generated       | 2026-08-03                      |

## Product Overview

Marker carriers

Signalling bracket, grey, unlabeled, mounting class: plug-in, usable surface: 4 x 10.5 mm

Signalling holder, Insertable into the spring connection terminal blocks ST 1.5..., labelled with UC-TM 4, UC-TMF 4, UCT-TM 4, UCT-TMF 4, ZB 4 or ZBF 4, grey, unlabelled, mounting type: plugged in, text field height: 10.5 mm, text field width: 4 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0810575

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 162 (C-3-2017)

GTIN 4017918877941

Weight per Piece (excluding packing) 0.370 g

Custom tariff number 85389099

Country of origin DE (Germany)

Dimensions

Length (b) 24.9 mm

Width (a) 4 mm

Height (c) 28.6 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

General

Color gray

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

Marking mounting type Plug in

Standards and Regulations

Flammability rating according to UL 94 V2

Classifications

eCl@ss 4.0 24190208 eCl@ss 4.1 24190208 eCl@ss 5.0 27149103 eCl@ss 5.1 27141100 eCl@ss 6.0 27149100 eCl@ss 7.0 27149153 eCl@ss 8.0 27149153 eCl@ss 9.0 27144075

ETIM 2.0 EC000761 ETIM 3.0 EC000761 ETIM 4.0 EC000761 ETIM 5.0 EC002248

UNSPSC 6.01 30211811 UNSPSC 7.0901 39121410 UNSPSC 11 39121410 UNSPSC 12.01 39121410 UNSPSC 13.2 39131505

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STP 4-2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.