

INDUSTRIAL COMPONENT DATA

TMT 4 R CUS 0824476 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: TMT 4 R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	TMT 4 R CUS
Catalog number	0824476
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-8E7BD14F00
Generated	2026-07-31

Product Overview

Marker for terminal blocks

Marker for terminals, available: by lines, white, labeled according to customer specifications, mounting type: fit in universal label slot, fit in flat index slot, for terminal width: 4.2 mm, usable area: 6.35x4.15mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0824476

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 94 (C-5-2013)

GTIN 4046356354820

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 6.35 mm

Width (a) 4.15 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C / 50 % relative humidity
General
Color white
Base element material Polyester foil
Type flat
Components free from silicone and halogen
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels per row 24
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 175 µm
Marking mounting type snap into universal marker groove
Standards and Regulations
Wipe res...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TMT 4 R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.