

## INDUSTRIAL COMPONENT DATA

# UC-TM 6 CUS 0824589 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-TM 6 CUS



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | UC-TM 6 CUS                  |
| Catalog number  | 0824589                      |
| Category        | Labelling for terminal block |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-B80BF6A88B                |
| Generated       | 2026-07-31                   |

## Product Overview

Marker for terminal blocks

Terminal marker, available: by mats, white, labeled according to customer's instructions, mounting class: fit in groove for high index, for terminal width: 6.2 mm, usable surface: 5.6 x 10.5 mm, Number of individual indices: 80

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, Number of individual labels: 80

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Labeled terminal marker

Pitch 6.2 mm

Type high

Data management status

Article revision 02

Marking

Number of individual labels 80

Number of individual labels per row 10

Identification technology UV LED technology

MountingMounting type snap into tall marker groove

Material specificationsRoHS compliant yes

Color white (RAL 9010)

Material PA

Flammability rating according to UL 94 V2

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 2

Components free from silicone and halogen

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

Dimensions Width 6 mm

Pitch 6.2 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-TM 6 CUS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.