

**INDUSTRIAL COMPONENT DATA**

# UC-TM 8 GN 0818412 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-TM 8 GN



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | UC-TM 8 GN                   |
| Catalog number  | 0818412                      |
| Category        | Labelling for terminal block |
| Minimum order   | 10 Pcs                       |
| Document ID     | EO-80E9A03BF8                |
| Generated       | 2026-08-04                   |

## Product Overview

Marker for terminal blocks

Marker for terminals, Mat, green, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting class: interlock, for terminal width: 8.2 mm, useful surface: 7.6 x 10.5 mm, Number of individual indexes: 56

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0818412

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 118 (C-3-2017)

GTIN 4046356135504

Weight per Piece (excluding packing) 12.900 g

Custom tariff number 39269097

Country of origin PL (Poland)

Dimensions

Width (a) 8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Note Can be labeled with CMS

Color green

Type high

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 56

Number of individual labels per row 7

Printability UV LED technology

Device 5147999 BLUEMARK CLED

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type snap into tall marker groove

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 28,2%

Class I 3

Class F 2

R22 HL 1 - HL 2

R23 HL 1 - HL 2

R24 HL 1 - HL 2

Standards and Regulations

Wipe resistance DIN....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-TM 8 GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.