

INDUSTRIAL COMPONENT DATA

SK U WH:UNGESTANZT 0800129 PHOENIX CONTACT Marker sheet

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U WH:UNGESTANZT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U WH:UNGESTANZT
Catalog number	0800129
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-C99701F848
Generated	2026-08-05

Product Overview

Marker sheet

Identification sheet, DIN A4, white, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems: without printing, mounting type: glued, for terminal width: 210 mm, useful surface: 296x210mm, Number of individual indexes: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0800129

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 346 (C-3-2017)

GTIN 4017918005733

Weight per Piece (excluding packing) 15.580 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 296 mm

Width (a) 210 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 0 °C

Recommended storage conditions 20-25 °C / 40-50 % relative humidity.

General

Note Print image may vary depending on laser printer

Color white

Type adhesive

Material Polyester

Adhesive Acrylic

Printability Office printing systems

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO₂ test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Adhesive strength 20 µm

Marking mounting type adhesive

Environmental Product Compliance

China RoHS For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U WH:UNGESTANZT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.