


INDUSTRIAL COMPONENT DATA

UM1U-TM (6X10) RD 0833045 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM1U-TM (6X10) RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM1U-TM (6X10) RD
Catalog number	0833045
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-2A2B6F8081
Generated	2026-08-06

Product Overview

Marker for terminal blocks

Markers for labeling terminals of the companies Weidmüller, Conta Clip and Klemsan, 20 units, displaced foot, not labeled, labelable with THERMOMARK CARD and BLUEMARK, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 0833045

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 178 (C-3-2017)

GTIN 4046356984874

Weight per Piece (excluding packing) 2.040 g

Custom tariff number 39269097

Country of origin PL (Poland)

Dimensions

Length (b) 10 mm

Width (a) 6 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

General

Color red

Type high

Components free from silicone, halogen, and cadmium

Flammability rating according to UL 94 V2

Material PC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printability Thermal transfer

Device 5146464 THERMOMARK CARD

Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions IEC 61010-1:2010-06

Result Test passed

Marking mounting type clip on

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V2

Classifications

eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.027141137eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM1U-TM (6X10) RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.