

INDUSTRIAL COMPONENT DATA

SD-WMTBS (NEUTRAL) VA 0826666 PHOENIX CONTACT

Conductor marking collar

Brand: PHOENIX CONTACT | Manufacturer Part Number: SD-WMTBS (NEUTRAL) VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SD-WMTBS (NEUTRAL) VA
Catalog number	0826666
Category	Cable coding system
Minimum order	50 Pcs
Document ID	EO-9CB8DA0E18
Generated	2026-07-29

Product Overview

Conductor marking collar

Conductor identification sleeve, silver: no printing, mounting class: slip, cable diameter range: 1 ... 63 mm, usable surface: 5.5 x 4 mm

Conductor marking collar, silver: without print, mounting type: slide-on, cable diameter range: 1 ... 63 mm, text field height: 4 mm, text field width: 5.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Marking strip/label

Marking

Printing without print

MountingMounting type slide-on

Material specificationsColor silver

Material Stainless steel

Environmental and real-life conditionsScratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements >= 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-1):2011-07

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Ambient conditions

Ambient temperature (operation) -80 °C ... 400 °C

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 % (Storage in a dry and dark place in the original packaging is recommended)

Shelf life 24 months

DimensionsWidth 5.5 mm

Text field width 5.50 mm

Text field height 4.00 mm

Length 10.9 mm

External dimensions

Outside diameter 16 mm ... 305 mm

Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)

NotesGeneral Please specify the required marking with order: Minimum order per imprint: 1 packing unit

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SD-WMTBS (NEUTRAL) VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.