

INDUSTRIAL COMPONENT DATA

RV 8-TP(2,4X0,8)L 3191013 PHOENIX CONTACT Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: RV 8-TP(2,4X0,8)L



Manufacturer	PHOENIX CONTACT
MPN / Reference	RV 8-TP(2,4X0,8)L
Catalog number	3191013
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-C16E091FA3
Generated	2026-07-29

Product Overview

Marshalling panel

Switching distributor, nominal voltage: 250 V, nominal current: 5 A, cross-section: 0.22 mm² - 0.56 mm², AWG: 20 - 24, connection type: TERMI-POINT®, number of poles: 1, number of connections: 16, width: 7.6 mm, length: 202 mm, color: gray, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3191013

Packing unit 5 pc

Catalog page Page 578 (C-3-2013)

GTIN 4017918093426

Weight per Piece (excluding packing) 68.110 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 16

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current I_N 5 A

Max. load current 5 A

Nominal voltage U_N 250 V

Open side panel No

Number of positions 1

Dimensions

Width 7.6 mm

Length 202 mm

Height NS 35/7,5 81.5 mm

Height NS 35/15 89 mm

Connection data

Conductor cross section solid min. 0.22 mm²

Conductor cross section solid max. 0.56 mm²

Conductor cross section flexible min. 0.22 mm²

Conductor cross section flexible max. 0.56 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 20

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Connection method TERMI-POINT®

TERMI-POINT pin dimensions 2.4 x 0.8 mm

Position of the TERMI-POINT pin vertical

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141124eCl@ss 4.127141124eCl@ss 5.027141124eCl@ss 5.127141100eCl@ss 6.0271411...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RV 8-TP(2,4X0,8)L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.