

INDUSTRIAL COMPONENT DATA

PTRV 4 BU/BU 3270118 PHOENIX CONTACT Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTRV 4 BU/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTRV 4 BU/BU
Catalog number	3270118
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-3A8887BF7D
Generated	2026-08-03

Product Overview

Marshalling panel

Switching distributor, nominal voltage: 250 V, nominal current: 10 A, connection type: Push-in connection, 1., 2., 3. and 4th floor, Sizing section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, color: blue, connection elements color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3270118

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 44 (C-1-2017)

GTIN 4046356796118

Weight per Piece (excluding packing) 17.070 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 4

Number of connections 16
Potentials 4
Nominal cross section 1.5 mm²
Color blue
Color of connection elements blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)
Maximum load current 10 A (with 1.5 mm² conductor cross section)
Nominal current I_N 10 A
Nominal voltage U_N 250 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire prot...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTRV 4 BU/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.