

**INDUSTRIAL COMPONENT DATA**

# FTRV 4 BU/BU 3270172 PHOENIX CONTACT Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTRV 4 BU/BU



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | FTRV 4 BU/BU                |
| Catalog number  | 3270172                     |
| Category        | Feed-through terminal block |
| Minimum order   | 10 Pcs                      |
| Document ID     | EO-A7F656914C               |
| Generated       | 2026-08-04                  |

## Product Overview

Marshalling panel

Switching distributor, without drive compressor, nominal voltage: 250 V, nominal current: 10 A, connection type: Push-in connection, 1., 2., 3. and 4th floor, Dimensioning section: 1.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting: NS 35/7.5, NS 35/15, colour: blue, connection element colour: blue

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Enclosures connectivity

## Additional Product Information

Key Commercial Data

Orderkey 3270172

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 44 (C-1-2017)

GTIN 4046356796293

Weight per Piece (excluding packing) 15.910 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 4  
Number of connections 16  
Potentials 4  
Nominal cross section 1.5 mm<sup>2</sup>  
Color blue  
Color of connection elements blue  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)  
Maximum load current 10 A (with 1.5 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 10 A  
Nominal voltage U<sub>N</sub> 250 V  
Open side panel Yes  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg  
Fire protection for rail vehicles (DIN E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTRV 4 BU/BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.