

INDUSTRIAL COMPONENT DATA

MBK-FS/FS 1406014 PHOENIX CONTACT Mini feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MBK-FS/FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MBK-FS/FS
Catalog number	1406014
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-5849B9F814
Generated	2026-08-05

Product Overview

Mini feed-through terminal block

Feed-in mini-terminal block, nominal voltage: 400 V, nominal current: 16 A, 1st floor, connection type: Flat plug connection, cross-section: 0.5 mm² - 1 mm², mounting: NS 15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 1406014

Packing unit 200 pc

Note Made to Order (non-returnable)

Catalog page Page 313 (CL-2005)

GTIN 4017918021023

Weight per Piece (excluding packing) 2.080 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 8

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection method Slip-on connection

Connection in acc. with standard IEC 60947-7-1

Maximum load current 16 A (current data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)

Nominal current I_N 16 A (current data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)

Nominal voltage U_N 400 V (voltage data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)

Open side panel No

Dimensions

Width 5.2 mm

Length 22 mm

Connection data

Connection method Slip-on connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 1 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 18

Conductor cross section flexible min. 0.5 mm²

Conductor cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MBK-FS/FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.