


INDUSTRIAL COMPONENT DATA

MC 0,5/ 7-G-2,5 AU 1973327 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 0,5/ 7-G-2,5 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 0,5/ 7-G-2,5 AU
Catalog number	1973327
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-1D5A5F828A
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 0.5 mm², color: green, nominal current: 4 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: MC 0.5/.. -G, pitch: 2.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.8 mm, number of soldering pins per potential: 1, plug-in system: COMBICON FK-MC 0.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

PCB base socket, nominal cross-section: 0.5 mm², colour: green, rated current: 4 A, dimensioning voltage (III/2): 160 V, contact surface: Au, contact connection type: plug, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, product series: MC 0.5/.. -G, pitch: 2.5 mm, mounting: Wave soldering, pin layout: Linear pinning, pin length [P]: 3.8 mm, number of solder pins per potential: 1, plug system: COMBICON FK-MC 0.5, Insertion pin orientation: Standard, locking: none, fastening type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1973327

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918961558

Weight per Piece (excluding packing) 1.450 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 10.1 mm

Width 19.4 mm

Pitch 2.5 mm

Dimension a 15 mm

Width [w] 19.4 mm

Height [h] 11.9 mm

Height 8.1 mm

Length of the solder pin 3.8 mm

Length 10.1 mm

General

Range of articles MC 0,5/...-G

Rated voltage (III/3) 80 V

Connection in acc. with standard EN-VDE

Nominal current IN 4 A

Color green

Number of positions 7

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1973327 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

7

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

2.5 mm

Modular spacing connections (EF006827)

2.5 mm

Rated current In (EF008250)

4 A

Rated voltage (EF000228)

160 V

Rated surg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 0,5/ 7-G-2,5 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.