

**INDUSTRIAL COMPONENT DATA**

# HCS-C MINI-P 1W C C C 7035 2203153 PHOENIX CONTACT

## Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI-P 1W C C C 7035



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | HCS-C MINI-P 1W C C C 7035 |
| Catalog number  | 2203153                    |
| Category        | Electronic enclosure       |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-C85CFFD86F              |
| Generated       | 2026-08-06                 |

### Product Overview

Electronic housing

C-Mini-Plus portable case in light gray, consisting of two halves with screws, 1.1 mm front with reinforcement, with window and keyboard slot

Light grey C-Mini-Plus portable case, consisting of two half-shells with screws, 1.1 mm recessed front, with window and keyboard opening

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2203153

Packing unit 1 pc

GTIN 4055626377063

Weight per Piece (excluding packing) 93.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-C MINI-P 1W C C C 7035

Order No. 2203153

Housing type Handheld housing

Type straight

Battery compartment no

Measurements

Dimensional drawing

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [ w ] 80 mm

Height [ h ] 135 mm

Depth [ d ] 29 mm

Diagonal 2.8 in. (Window for display)

Dimensions 70.4 mm x 69.2 mm x 1.1 mm (Recessed area on front)

70.4 mm x 8.2 mm x 1.1 mm (Recessed area on front)

63 mm x 34 mm (Window for display)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSP...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI-P 1W C C C 7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.