

INDUSTRIAL COMPONENT DATA

UCS CC 7035 2203395 PHOENIX CONTACT Corner inlay

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS CC 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS CC 7035
Catalog number	2203395
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-6566574DDA
Generated	2026-08-05

Product Overview

Corner inlay

Angular insert for UCS boxes; Material: Polyamide; Colour: light grey, similar to RAL 7035

Corner inlay for UCS housings, material: polyamide, color: light gray, similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Select corner

Housing type Universal housings

Housing series UCS

Type including screws, flat

Ventilation openings present no

Data management status

Article revision 00

DimensionsWidth 16.2 mm

Height 16.2 mm

Depth 13.5 mm

PCB design

PCB thickness 0.8 mm ... 3 mm

Material specificationsColor (Housing) light gray (RAL 7035)

Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Insulating material PA
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditions Vibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or varnish
Specification VW PV 3.10.7:2005-02
Re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS CC 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.