

INDUSTRIAL COMPONENT DATA

MC 1,5/12-ST-3,81 BDS:24-13 X7 1709951 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/12-ST-3,81 BDS:24-13 X7



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/12-ST-3,81 BDS:24-13 X7
Catalog number	1709951
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-E41D10B60E
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Female connection, Number of potentials: 12, Number of rows: 1, Number of poles per row: 12, number of connections: 12, family of articles: MC 1.5/.. -ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksyst.: MINI COMBICON, Lock: without, packaging type: boxed

PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 12, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1709951

Packing unit 1

GTIN 4055626167671

Custom tariff number 85366990

Drawings

Electrical parameters

Material data - contact

Dimensions for the product

Ambient conditions

Pull-out test

Air clearances and creepage distances

Durability tests (B)

Environmental and durability tests (E)

Classifications

Item properties

Connection capacity

Material data - housing

Packaging information

Termination and connection method

Mechanical tests according to standard

Mechanical tests (A)

Climatic tests (D)

Environmental Product Compliance

Drawings

Diagram

Type: MC 1,5/...-ST-3,81 with MC 1,5/...-G-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with MC 1,5/...-G-3,81 THT

Diagram

Type: MC 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81 P26 THR

Diagram

Type: MC 1,5/...-ST-3,81 with MCD 1,5/...-G1-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with MCDV 1,5/...-G1-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with MCVU 1,5/...-GFD-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with MCO 1,5/...-GR-3,81

Diagram

Type: MC 1,5/...-ST-3,81 with IMC 1,5/...-ST-3,81

Back to topItem properties

Brief article description Printed-circuit board connector

Plug-in system MINI COMBICON

Type of contact Female connector

Range of articles MC 1,5/...-ST

Pitch 3.81 mm

Number of positions 12

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Number of levels 1

Number of connections 12

Number of potentials 12

[Back to top](#)Electrical paramet...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/12-ST-3,81 BDS:24-13 X7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.