

INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 2-G-5,08 GY7031 1751260 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 2-G-5,08 GY7031



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 2-G-5,08 GY7031
Catalog number	1751260
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-22DFC42945
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 2.5 mm², color: bluish gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, type of contact: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MSTBVA 2.5/. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed
PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 2, pitch: 5.08 mm, color: blue grey, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1751260

Packing unit 1

GTIN 4046356315876

Custom tariff number 85366930

Drawings

General

[Environmental Product Compliance](#)

[Dimensions](#)

[Standards and Regulations](#)

[Classifications](#)

[Drawings](#)

[Diagram](#)

Type: TFKC 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08

[Back to top](#)[Dimensions](#)

Length [l] 8.57 mm

Width 12.16 mm

Pitch 5.08 mm

Dimension a 5.08 mm

Width [w] 12.16 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.57 mm

[Back to top](#)[General](#)

Range of articles MSTBVA 2,5/...-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Color blue grey

Number of positions 2

[Back to top](#)[Standards and Regulations](#)

Connection in acc. with standard EN-VDE

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

[Back to top](#)[ETIM](#)

ETIM 3.0 EC001121

ETIM 4.0 EC002637

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 30211810
UNSPSC 7.0901 39121409
UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409
UNSPSC 18.0 39121409
UNSPSC 19.0 39121409
UNSPSC 20.0 39121409
UNSPSC 21.0 39121409

Back to top

ETIM for 1751260 Connectors (EC002637)

Feature Name

Feature Value

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 2-G-5,08 GY7031 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.