

INDUSTRIAL COMPONENT DATA

MC 1,5/ 2-G-3,81 PIN 8,6 1707044 PHOENIX CONTACT Base housing, rated current: 8 A, number of poles: 2, pitch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 2-G-3,81 PIN 8,6



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 2-G-3,81 PIN 8,6
Catalog number	1707044
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-70C1D28472
Generated	2026-08-06

Product Overview

Base housing, rated current: 8 A, number of poles: 2, pitch: 3.81 mm, color: green, contact surface: Tin, mounting: Wave soldering

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MC 1.5/.. -G, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 8.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Header, nominal current: 8 A, number of positions: 2, pitch: 3.81 mm, color: green, contact surface: Tin, mounting: Wave soldering

Your advantages

Well-known mounting principle allows worldwide useMaximum flexibility when it comes to device design - one header for connectors with different connection technologiesKey Commercial Data

Orderkey 1707044

Packing unit 1

GTIN 4046356895514

Custom tariff number 85366930

General

Range of articles MC 1,5/..-G

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color green

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCl@ss

eCl@ss 5.1 27260701

eCl@ss 6.0 27260704

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

UNSPSC

UNSPSC 13.2 39121409

ETIM for 1707044 Connectors (EC002637)

Feature Name**Feature Value**

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 2-G-3,81 PIN 8,6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.