

INDUSTRIAL COMPONENT DATA

MC 1,5/ 3-G-3,5 OG 1371441 PHOENIX CONTACT Printed circuit board base housing, nominal section: 1.5 mm², col..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 3-G-3,5 OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 3-G-3,5 OG
Catalog number	1371441
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-6D6D44C590
Generated	2026-08-03

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm², color: orange, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 3, screw clamping shape: L Longitudinal slot, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, packaging type: boxed

Base housing printed circuit board, nominal section: 1.5 mm², rated current: 8 A, sizing voltage (III/2): 160 V, contact type: Male, number of rows: 1, screw clamping shape: L Longitudinal groove, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of welding pins per potential: 1, plug-in system: MINI COMBICON, Plug-in face orientation: Standard, Lock: without, fixing type: without, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1371441 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

3.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Orange

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 3-G-3,5 OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.