

INDUSTRIAL COMPONENT DATA

SAC-4P-10,0-PUR/M 8FS SH NC 1579019 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-10,0-PUR/M 8FS SH NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-10,0-PUR/M 8FS SH NC
Catalog number	1579019
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-56EB5EF120
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, to Straight connection female M8, coding: A, The screen is not placed in the knurling

Sensor/actuator cable, halogen-free PUR, grey-black RAL 7021, shielded, free conductor end, on M8 straight socket, coding: A, Shield not connected to ring nut

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1579019

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356481410

Weight per Piece (excluding packing) 345.200 g

Custom tariff number 85444290

Country of origin PL (Poland)

General

Rated voltage 48 V AC

60 V DC
Coding A - standard
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LiF9YC11Y
UL AWM style 20549
Conductor cross section 4x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)
Thickness, insulation ≥ 0.21 mm (Core insulation)
approx. 0.5 mm (Outer cable sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Shielding Braided copper wires
Optical shield covering 80 %
External sheath, color black-gray RAL 7021
External cable diameter D 4.7 mm ±0.15 mm
Smallest bending radius, fixed installation 24 mm
Smallest bending radius, movable installation 48 mm
Number of bending cycles 10000000
Bending radius 48 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 31 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance ≥ 100 GΩ·km (at 20 °C)
Conductor resistance max. 78 Ω/km (at 20 °C)
Nominal voltage, cable ≤ 300 V
Test voltage, cable ≥ 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-10,0-PUR/M 8FS SH NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.