

INDUSTRIAL COMPONENT DATA

HCS-C MINI-P 1W 2AA C C 7035 2203157 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI-P 1W 2AA C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI-P 1W 2AA C C 7035
Catalog number	2203157
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-7BACBCB26F
Generated	2026-08-05

Product Overview

Electronic housing

C-Mini-Plus portable case in light gray, formed by two halves, screws. Front with 1.1 mm reinforcement, with window and keyboard slot, battery compartment cover and battery contacts for 2 AA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203157

Packing unit 1 pc

GTIN 4055626377094

Weight per Piece (excluding packing) 93.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-C MINI-P 1W 2AA C C 7035

Order No. 2203157

Housing type Handheld housing

Type straight

Battery compartment 2 x AA

Measurements**Dimensional drawing**

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [w] 80 mm

Height [h] 135 mm

Depth [d] 29 mm

Diagonal 2.8 in. (Window for display)

Dimensions 70.4 mm x 69.2 mm x 1.1 mm (Recessed area on front)

70.4 mm x 8.2 mm x 1.1 mm (Recessed area on front)

63 mm x 34 mm (Window for display)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 11391214...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI-P 1W 2AA C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.