

INDUSTRIAL COMPONENT DATA

MC 1,5/ 5-GF-3,5 BK 1350387 PHOENIX CONTACT Printed circuit board base housing, nominal section: 1.5 mm², co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 5-GF-3,5 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 5-GF-3,5 BK
Catalog number	1350387
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-745924F220
Generated	2026-08-05

Product Overview

MC 1,5/ 5-GF-3,5 BK 1350387 PHOENIX CONTACT Printed circuit board base housing, nominal section: 1.5 mm², co..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	3.5 mm
Modular spacing connections (EF006827)	3.5 mm
Rated current I _n (EF008250)	8 A
Rated voltage (EF000228)	160 V
Rated surge voltage (EF002993)	2.5 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Tin
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.2 mm
Length pin (EF006825)	3.4 mm
Material insulation body (EF007543)	Other

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	Black
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 5, family of articles: MC 1.5/.. -GF, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, clamping type: Air clamping (thread), packaging type: boxed

Connector for printed circuit board, nominal section: 1.5 mm², color: black, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 5, article family: MC 1,5/.. -GF, pitch: 3.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, plug-in system: MINI COMBICON, Plug-in face orientation: Standard, Locking: Screw lock, fixing type: Aerial fastening (thread), packaging type: box packaging: Boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 5-GF-3,5 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.