

INDUSTRIAL COMPONENT DATA

TTC-6-1X2-24DC-UT 2906798 PHOENIX CONTACT Surge protection for a 2-wire floating signal circuit, e.g., 0(4) ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-1X2-24DC-UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-1X2-24DC-UT
Catalog number	2906798
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-0376547F67
Generated	2026-08-06

Product Overview

Surge protection for a 2-wire floating signal circuit, e.g., 0(4) ... 20 mA current loop, HART-compatible.
Surge protection for a potential-free 2-wire signal circuit, e.g. current loop 0(4) ... 20 mA, suitable for HART.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data
Orderkey 2906798
Packing unit 1 pc
Catalog page Page 118 (C-4-2019)
GTIN 4055626135533
Weight per Piece (excluding packing) 40.000 g
Custom tariff number 85363010
Country of origin DE (Germany)
Drawings
Ambient conditions
Protective circuit
Connection data
Environmental Product Compliance
Dimensions

[General](#)[Additional technical data](#)[Standards and Regulations](#)[Classifications](#)[Drawings](#)[Diagram](#)[Dimensional drawing](#)[Pictogram](#)[Circuit diagram](#)[Back to top](#)[Dimensions](#)

Height 105.8 mm

Width 6.2 mm +0.1 mm

Depth 69.5 mm (incl. DIN rail 7.5 mm)

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Altitude ≤ 4000 m (amsl (above mean sea level))

Degree of protection IP20

[Back to top](#)[General](#)

Housing material PBT

Flammability rating according to UL 94 V-0

Color traffic grey A RAL 7042

Mounting type DIN rail: TH 35 - 7.5 mm

Type DIN rail module, one-piece

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

[Back to top](#)[Protective circuit](#)

IEC test classification C1

C2

C3

D1

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 30 V DC

21 V AC

Rated current 600 mA (40 °C)

Operating effective current I_{Cat UC} ≤ 5 μAResidual current I_{PE} ≤ 1 μANominal discharge current I_{n(8/20)} μs (line-line) 5 kANominal discharge current I_{n(8/20)} μs (line-earth) 5 kAPulse discharge current I_{imp(10/350)} μs (line-lin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-1X2-24DC-UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.