

**INDUSTRIAL COMPONENT DATA**

# MC 1,5/ 5-ST-3,81 BD:TX-GN 1460867 PHOENIX CONTACT

## Printed circuit board connector, nominal section: 1.5 mm2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 5-ST-3,81 BD:TX-GN



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | MC 1,5/ 5-ST-3,81 BD:TX-GN |
| Catalog number  | 1460867                    |
| Category        | Cable connector            |
| Minimum order   | 1000 Pcs                   |
| Document ID     | EO-41B13F840A              |
| Generated       | 2026-08-03                 |

### Product Overview

Printed circuit board connector, nominal section: 1.5 mm2, color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of rows: 1, number of poles: 5, family of articles: MC 1.5/..-ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, plug-in system: COMBICON MC 1.5, lock: without, clamping type: without, packaging type: boxed  
Printed circuit board connector

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT > PCB Connectors (PCC)

### Additional Product Information

ETIM for 1460867 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Angle contact/conductor connection (EF007546)

Other

Rated current  $I_n$  (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm<sup>2</sup>

Connectable conductor cross section solid-core (EF007337)

0.14 mm<sup>2</sup>

Type of electric connection (EF003961)

Screw connection

Connectable cable type (EF006816)

Tubular cable

Material of contact surface (EF004020)

Tin

Material contact (EF007544)

Copper

Material insulation body (EF007543)

Polyamide (PA)

Housing material (EF001596)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 5-ST-3,81 BD:TX-GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.