

INDUSTRIAL COMPONENT DATA

MC 1,5/ 6-G-3,5-RN P26THTR44 1786798 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 6-G-3,5-RN P26THTR44



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 6-G-3,5-RN P26THTR44
Catalog number	1786798
Category	Printed circuit board connector
Minimum order	330 Pcs
Document ID	EO-781BF4E632
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base case, color: black, contact surface: Tin, number of poles: 6, article family: MC 1.5/.. -G-RN, pitch: 3.5mm, pin arrangement: Linear pin arrangement, pin length [P]: 2.6mm, packing type: 44mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1786798

Packing unit 1

GTIN 4046356692441

Custom tariff number 85366930

Dimensions

Length [l] 9.2 mm

Width 24.6 mm

Pitch 3.5 mm

Dimension a 17.5 mm

Width [w] 24.6 mm

Height [h] 9.85 mm

Height 7.25 mm

Length of the solder pin 2.6 mm

Length 9.2 mm

General

Range of articles MC 1,5/-G-RN

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Maximum load current 8 A

Insulating material PA-GF

Flammability rating according to UL 94 V0

Color black

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 6-G-3,5-RN P26THTR44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.