

INDUSTRIAL COMPONENT DATA

GW PL DP/MODBUS 2316365 PHOENIX CONTACT Protocol converter

Brand: PHOENIX CONTACT | Manufacturer Part Number: GW PL DP/MODBUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	GW PL DP/MODBUS
Catalog number	2316365
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-25A28CE720
Generated	2026-08-04

Product Overview

Protocol converter
Modbus/RTU to PROFIBUS DP Protocol Converter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Technical dataNotesNote on application
Note on application Only for industrial use
Utilization restriction
EMC note EMC: class A product, see manufacturer's declaration in the download area
Product propertiesProduct type Interface converter
Data management status
Article revision 03
Insulation characteristics
Overvoltage category II
Degree of pollution 2
Electrical propertiesSupply
Supply voltage range 18 V DC ... 30 V DC
Nominal supply voltage 24 V DC
Max. current consumption 60 mA

Connection dataSupply

Connection method COMBICON plug-in screw terminal block

Conductor cross section, flexible 0.20 mm² ... 2.50 mm²

Conductor cross section, rigid 0.20 mm² ... 2.50 mm²

Conductor cross section AWG 24 ... 12

Tightening torque 0.5 Nm ... 0.6 Nm

InterfacesSignal Modbus

Data: PROFIBUS DP

Data rate 9.6 kbps (min.)

12 Mbps (max.)

Number of connections 2

Connection method D-SUB-9, COMBICON

No. of channels 1

Tightening torque 0.5 Nm ... 0.6 Nm

Connection technology Screw connection

Termination resistor 390 Ω - 220 Ω - 390 Ω (switchable)

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section, rigid max. 2.5 mm²

Conductor cross section, rigid min. 0.2 mm²

Conductor cross section AWG max. 12

Conductor cross section AWG min. 24

Protocols supported Modbus/RTU, PROFIBUS DP

Data: Modbus/RTU

Transmission speed 1200 kbps (min.)

Data rate 115.2 kbps (max.)

Number of connections 2

Connection method COMBICON

No. of channels 4 (Modbus/RTU....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GW PL DP/MODBUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.