

INDUSTRIAL COMPONENT DATA

MC 1,5/ 8-G-3,5 AU 1858316 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 8-G-3,5 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 8-G-3,5 AU
Catalog number	1858316
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-F8C9BEE632
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MC 1.5/.. -G, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1858316

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918228071

Weight per Piece (excluding packing) 2.230 g

Custom tariff number 85366990

Country of origin DE (Germany)

Item properties

Brief article description Feed-through header

Plug-in system MINI COMBICON

Type of contact Male connector

Range of articles MC 1,5/..-G

Pitch 3.5 mm

Number of positions 8

Mounting type Wave soldering

Pin layout Linear pinning

Locking without

Number of levels 1

Electrical parameters

Rated current 8 A

Rated insulation voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Selective coating

Metal surface contact area (top layer) Gold (0.8 - 1.4 μm Au)

Metal surface contact area (middle layer) Nickel (2 - 3 μm Ni)

Metal surface soldering area (top layer) Gold (0.8 - 1.4 μm Au)

Metal surface soldering area (middle layer) Nickel (2 - 3 μm Ni)

Material data - housing

Insulating material PBT

Insulating material group IIIa

CTI according to IEC 60112 225

Flammability rating according to UL 94 V0

Dimensions for the product

Length [l] 9.2 mm

Width [w] 29.4 mm

Height [h] 10.65 mm

Pitch 3.5 mm

Height (without solder pin) 7.25 mm

Solder pin [P] 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Dimension a 24.5 mm

Packaging information

Type of packaging packed in cardboard

Pieces per...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 8-G-3,5 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.