


INDUSTRIAL COMPONENT DATA

MC 1,5/ 8-GF-3,81 BK 1703032 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 8-GF-3,81 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 8-GF-3,81 BK
Catalog number	1703032
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-01233CD590
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Male, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, family of articles: MC 1.5/.. -GF, pitch: 3.81 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, Stecksystem: MINI COMBICON, Locking:Screw locking, packaging type: boxed

Printed circuit board base housing, nominal section: 1.5 mm², nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MC 1.5/.. -GF, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1703032

Packing unit 1

GTIN 4046356633598

Custom tariff number 85366930

Dimensions

Length [l] 9.2 mm

Width 40.87 mm

Pitch 3.81 mm

Dimension a 26.67 mm

Width [w] 40.87 mm

Height [h] 10.3 mm

Height 6.9 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 9.2 mm

General

Range of articles MC 1,5/...-GF

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color black

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send PHOENIX CONTACT / MC 1,5/ 8-GF-3,81 BK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.**GLOBAL OFFICES**Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, DubaiCatalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.