

INDUSTRIAL COMPONENT DATA

MC 1,5/ 8-STF-3,81 BU BD:-9Q 1010157 PHOENIX CONTACT

Printed-circuit board connector MC 1,5/ 8-STF-3,81 BU B..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 8-STF-3,81 BU BD:-9Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 8-STF-3,81 BU BD:-9Q
Catalog number	1010157
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-0C7C32D506
Generated	2026-08-05

Product Overview

Printed-circuit board connector - MC 1,5/ 8-STF-3,81 BU BD:-9Q - 1010157

Connector for printed circuit board, nominal section: 1.5 mm², color: blue, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, article family: MC 1,5/..-STF, pitch: 3.81 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksystem: MINI COMBICON, Lock: Locking by screw, type of packaging: packed in box

PCB connector, nominal cross section: 1.5 mm², color: blue, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 8, number of rows: 1, number of positions: 8, number of connections: 8, product range: MC 1,5/..-STF, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors S

Product type PCB connector

Product family MC 1,5/..-STF

Number of positions 8

Pitch 3.81 mm

Number of connections 8
Number of rows 1
Number of potentials 8
Electrical propertiesNominal current I_N 8 A
Nominal voltage U_N 160 V
Degree of pollution 3
Contact resistance 1.3 m Ω
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MC 1,5
Nominal cross section 1.5 mm²
Contact connection type Socket
Interlock
Locking type Screw locking mechanism
Mounting flange Screw flange
Tightening torque 0.3 Nm
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG 28 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.75 mm²
2 conductors with same cross section, solid 0.08 mm² ... 0.5 mm²
2 conductors with same cross section, flexible 0.08 mm² ... 0.75 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.34 mm²
2 conductors with the same cross section, flex...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 8-STF-3,81 BU BD:-9Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.