

INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 2-G1-3,5 RNP26THRR32 1717225 PHOENIX CONTACT Housing base for printed circuit board, number of pol..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 2-G1-3,5 RNP26THRR32



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 2-G1-3,5 RNP26THRR32
Catalog number	1717225
Category	Printed circuit board connector
Minimum order	1100 Pcs
Document ID	EO-A6CA815B88
Generated	2026-08-06

Product Overview

Housing base for printed circuit board, number of poles: 2, pitch: 3.5 mm, color: black, surface of contact: Tin, assembly: Soldering THR

Base housing printed circuit board, nominal section: 1.5 mm², colour: black, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of potentials: 4, Number of rows: 2, Number of poles per row: 2, number of connections: 4, article family: MCDN 1.5/..-G1-RN-THR, pitch: 3.5 mm, mounting: Welding THR, pin arrangement: Linear pin arrangement, pin length [P]: 1.4 mm, Stecksystem: MINI COMBICON, Locking:Lace locking, packing type: 32 mm wide strap

PCB headers, nominal cross section: 1.5 mm², color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Pin, number of potentials: 4, number of rows: 2, number of positions: 2, number of connections: 4, product range: MCDN 1,5/..-G1-RN-THR, pitch: 3.5 mm, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: Snap-in locking, mounting: Engagement nose, type of packaging: 32 mm wide tape

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors S
Product type PCB headers

Product family MCDN 1,5/..-G1-RN-THR

Number of positions 2

Pitch 3.5 mm

Number of connections 4

Number of rows 2

Number of potentials 4

Pin layout Linear pinning

Solder pins per potential 1

Electrical propertiesNominal current IN 8 A

Nominal voltage UN 160 V

Degree of pollution 3

Contact resistance 2.1 m Ω

Rated voltage (III/3) 160 V

Rated surge voltage (III/3) 2.5 kV

Rated voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Rated voltage (II/2) 250 V

Rated surge voltage (II/2) 2.5 kV

MountingMounting type THR soldering

Pin layout Linear pinning

Processing notes

Process Reflow/wave soldering

Moisture Sensitive Level MSL 1

Classification temperature Tc 260 °C

Solder cycles in the reflow 3

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Tin-plated

Metal surface contact area (top layer) Tin (3 - 5 μm Sn)

Metal surface contact area (middle layer) Nickel (1 - 3 μm Ni)

Metal surface soldering area (top layer) Tin (3 - 5 μm Sn)

Metal surface soldering area (middle layer) Nickel (1 - 3 μm Ni)

Material data - housing

Color (Housing) black (9005)

Insulating material LCP

Insulating material group IIIa

CTI according to IEC 60112 175

Flammability rating according to UL 94 V0

NotesDetails for soldering processes Processing using reflow processes in compliance wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 2-G1-3,5 RNP26THRR32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.