


INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 6-G1-3,5RNP26THRCP61 1014704 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 6-G1-3,5RNP26THRCP61



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 6-G1-3,5RNP26THRCP61
Catalog number	1014704
Category	Printed circuit board connector
Minimum order	45 Pcs
Document ID	EO-E8FA8370CC
Generated	2026-08-06

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 2, number of poles: 6, number of connections: 12, family of articles: MCDN 1.5/.. -G1-RN-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1014704

Packing unit 1

GTIN 4055626495231

Custom tariff number 85366930

Dimensions

Length [L] 13.3 mm

Width 24.7 mm

Pitch 3.5 mm

Dimension a 17.5 mm

Width [w] 24.7 mm

Height [h] 17.8 mm

Height 15.2 mm

Length of the solder pin 2.6 mm

Pin dimensions 0.8 x 0.8 mm

Pin spacing 3.50 mm

Length 13.3 mm

General

Range of articles MCDN 1,5/..-G1-RN-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Maximum load current 8 A (per position)

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 5.0EC002637ETIM 6.0EC002637

ETIM for 1014704 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

12

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 6-G1-3,5RNP26THRCP61 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.